

Price list n.29C

Valid January 2019

language



Tractors



THE INTERNATIONAL CERTIFICATION NETWORK

CERTIFICATE

CISQ/ICIM SPA has issued an IQNet recognized certificate that the organization:

BCS S.p.A.

Head Office and Operative Unit
Viale Mazzini, 161 - I-20081 Abbiategrasso (MI)
Operative Units
Via Valbrina, 17119 - I-42045 Luzzara (RE)
Viale Europa, 59 - I-20090 Cusago (MI)

Quality Management System

for the following scope:

for the following scope:
Design, production and servicing of tractors, agricultural and green maintenance machines, engine driven welders, generating sets and tower light.

which fulfils the requirements of the following standard:

ISO 9001:2015

Issued on: 2018-03-06

First issued on: 1994-05-30

This attestation is directly linked to the IQNet Partner's original certificate and shall not be used as a stand-alone document.

Registration Number: IT-3722

Registration Number: IT-3722




Alex Stoichitoiu
President of IQNET




Ing. Claudio Provetti
President of CISQ

IQNet Partners*

AENOR Spain AFNOR Certification France APCER Portugal CCC Cyprus CSMO Italy
CQC China CQM QMS Czech Republic Cto Cert Croatia DQS Holding GmbH Germany FCBV Brazil
FONDONORMA Venezuela ICONTEC Colombia Inspecta Sertificanti Oy Finland INTECO Costa Rica
IRAM Argentina IQA Japan KQF Korea MIRTEC Greece MSZT Hungary Nestis AS Norway NSAI Ireland
NYCE-SIGE Mexico PCBQ Poland Quality Austria RINA RSCC SI Israel SIFQ Slovenia
SIREM QAS International Malaysia SQS Switzerland SRAC Romania TEST St Petersburg Russia TSE Turkey YUQS Serbia
ICONET is represented in the USA by: AFNOR Certification, CQC, DQS Holding GmbH and NSAI Inc.

* The list of IQNet partners is valid at the time of issue of this certificate. Updated information is available under www.iqnet-certification.com



CERTIFICATO n. 0192/8
 CERTIFICATE No. _____

SI CERTIFICA CHE IL SISTEMA DI GESTIONE PER LA QUALITÀ DI
WE HEREBY CERTIFY THAT THE QUALITY MANAGEMENT SYSTEM OPERATED BY

BCS S.p.A.

Sede e Unità Operativa

Viale Mazzini, 161 - 20081 Abbiategrasso (MI) - Italia
Uffici direzionali e amministrativi, progettazione, produzione e assistenza di macchine per agricoltura e manutenzione del verde
Unità Operative
Via Valbrina, 17/19 - 42045 Luzzara (RE) - Italia
Progettazione, produzione e assistenza di trattori
Viale Europa, 59 - 20090 Cusago (MI) - Italia
Progettazione, produzione e assistenza di motosilatrici e gruppi elettrogeni e torri faro

È CONFORME ALLA NORMA / IS IN COMPLIANCE WITH THE STANDARD

UNI EN ISO 9001:2015

Sistema di Gestione per la Qualità / Quality Management System

PER LE SEGUENTI ATTIVITÀ / FOR THE FOLLOWING ACTIVITIES

EA: 18

Progettazione, produzione ed assistenza di trattori, macchine per agricoltura e manutenzione del verde, motosaldatrici, gruppi elettrogeni e torri faro.
Design, production and servicing of tractors, agricultural and green maintenance machines, engine driven welders, generating sets and tower light.

Riferito alla documentazione del Sistema di Gestione per la Qualità aziendale per l'applicabilità dei requisiti della norme di riferimento.
Refer to the documentation of the Quality Management System for details of application to reference standard requirements.

Il presente certificato è soggetto all'aspetto del documento: "QM" (Regolamento per la certificazione dei sistemi di gestione) e al relativo Schema specifico.
The use and the validity of this certificate shall satisfy the requirements of the CNR document "Rules for the certification of company management systems" and specific Scheme.

For timely and updated information about any changes in the certification status referred to in this certificate, please contact the number +38-03 725341 or e-mail address info@pau.it.

Data emissione First issue	Emissione corrente Current issue	Data di scadenza Expiring date
30/05/1994	06/03/2018	05/03/2021

ICM S.p.A.
Piazza Don Enrico Magelli, 75 - 20099 Sesto San Giovanni (MI)
www.icm.it



Membro degli Accordi di Mutual
Riconoscimento EA, INF e ILAC
Signatory of EA, INF and ILAC Mutual
Recognition Agreements



NQSA, the association of the world's first class
 certification bodies, is the largest provider of manager
 system certification in the world.
 NQSA is composed of more than 30 bodies and runs



www.cisq.com

CISQ è la Federazione Italiana di Organismi
Certificazione dei sistemi di gestione aziendali
CISQ is the Italian Federation of management
system certification bodies

Approved by the Managing Director



GENERAL TERMS AND CONDITIONS

Premise

The following terms and conditions regulate the sale of machines and the relevant components between the Seller - BCS S.p.A. - and any Buyer.

Every different agreement from the present General Conditions will be effective only if accepted in writing expressly by the Seller.

Art. 1 - Orders.

1.1. Any order issued by the Buyer is subject to the written acceptance of the BCS S.p.A. Commercial Direction and the sale contract will be considered concluded, becoming binding between the Parties, when the confirmation is sent to the Buyer.

The confirmation sent by the BCS S.p.A. Commercial Direction defines and shows all the binding conditions and contents of the contract, integrally replacing itself with the order.

Should the confirmation contain additions, limitations or present other changes in comparison with the order, the assent of the Buyer will be considered as tacitly accepted, unless a written notice to be sent to the BCS S.p.A. Commercial Direction within 48 working hours from the receipt of the confirmation.

Such a missing notice will also involve the total acceptance of the present General Conditions by the Buyer, which will be the only ones entitled to govern the contract and will prevail -in any case- on the purchase conditions of the Buyer, if any.

The sending of the invoice to the Buyer, issued on the ground of the order, if prior to the receipt of the written confirmation, involves in any case the conclusion of the contract.

1.2. The Seller engages himself to deliver "ex factory" only the products listed in the order confirmation of the BCS S.p.A. Commercial Direction.

Art. 2 - Delivery.

2.1. The delivery time elapses from the date of sending the order confirmation to the Buyer or, if later, from the punctual and complete receipt of the whole documentation required to the Buyer, of the information and any explanation about the details of the order, particularly about all the technical questions or the supply of any necessary part.

2.2. The Seller is not responsible for any supply delay due to causes beyond control or any other circumstance beyond his will, such as traffic or work or current supply stops, strikes, shutdown, shortage of raw material, war events, unless otherwise agreed. If the Seller is not in a position to respect the expected delivery time due to one of the above situations, it will be postponed in accordance between the Parties; if the same impediment or any other one persists even after the postponed delivery time, the Seller reserves the right to withdraw from the contract.

2.3. The Buyer must collect the products from the Seller's warehouse within 30 days from the delivery time. This period is essential. After thirty days from the delivery time, if the products are not collected by the Buyer, the contract is to be intended as concluded due to the Buyer's non-compliance and any advanced payment will be ascribed to the Seller as a compensation, without prejudice to indemnity for any greater injury suffered. The Seller shall have the right to ask the Buyer the late fulfillment of the contract.

2.4. In any case the Buyer declares already now to accept a possible delivery delay of 30 working days. The Buyer can consider such a delay neither as breach of contract nor as delayed fulfillment.

Art. 3 - Prices, terms of payment, expiry.

3.1. Unless agreed differently in the order confirmation, the deliveries are meant "Ex factory"; all prices are in Euros, packing, insurance and VAT charges excluded.

3.2. If a different delivery place is agreed, the delivery must be effected "Free place of destination". In this case, the Buyer must organize the unloading process promptly; if not the additional costs will be invoiced separately.

GENERAL TERMS AND CONDITIONS

3.3. The transport is always intended to be effected on behalf, risk and danger of the Buyer, also when the transport should be effected by the Seller or his representative for any reason.

3.4. The goods will be insured only if the Buyer requires it in writing. In any case the insurance charges will be totally paid by the Buyer.

3.5. The prices are the ones listed in the Price List in force at the time of entering the order. Unless agreed differently, the payment must be effected within 90 days from the date of the invoice.

3.6. If, after the conclusion of the contract, the Seller becomes aware of a modification or a worsening of the financial situation of the Buyer which could jeopardize the fulfillment of the payment, the Seller shall have the right to suspend his service. Particularly this would involve, in case of even temporarily difficulties, the fulfillment of the payment obligations, in the event of foreclosure, protest of promissory notes or cheques. In all these cases, the Seller can grant the Buyer a period to offer any adequate guarantees and the failed respect of such a period will involve the withdrawal of the contract on the ground of the article 1456 of the Civil Code.

Art. 4 - Further modifications.

4.1. The Seller is free to bring any technical or set-up modifications to the products without prior information to the Buyer.

4.2. The Seller is not obliged to bring any modification to the products that have been or are being produced after confirming the order. Should the Seller accept any modification required in writing by the Buyer, any charge will be invoiced separately to the Buyer.

Art. 5 - Spare parts.

5.1. The Seller engages himself to supply the Distributor with the spare parts for the sold products. The spare part price will be the one of the price list in force at the time of entering the order for the spare part itself.

Art. 6 - Warranty.

6.1. The Seller guarantees the regular performance of the products, except for the parts subject to wear, for a period of two (2) years from the delivery date.

6.2. In any case, any damage or malfunction due to carelessness, failed or wrong maintenance, accidents, any use not complying with what described in the operator's manual are excluded from the warranty.

6.3. Warranty is limited to the reparation and/or replacement, without prejudice to any greater damages. The choice between reparation and/or replacement is an unappealable decision of the Seller. Also for the replaced or repaired components the original warranty period is still valid.

6.4. The reparation or any other maintenance service on the product must be exclusively held by the Seller or any other workshop authorized by the Seller, otherwise this will bring to the forfeiture of the warranty.

Art. 7 - Retention on title.

7.1. Should the payment be effected, totally or partially, by installments after the delivery, the products delivered to the Buyer will remain property of the Seller up to the total payment of the price (i.e. payment of the last installment) pursuant to and in accordance with Article 1523 of the Civil Code and following.

7.2. The failed payment in the agreed terms, even if one single installment exceeding the eighth of the price, i.e. the failed payment of two installments even if non-consecutive, includes the Seller's right to withdraw the contract effective from the date of the information to the Buyer as well as the Seller's right to declare the Buyer excluded from the benefit of the terms of payment and to pretend the immediate payment of the whole balance amount.

GENERAL TERMS AND CONDITIONS

7.3. In case of withdrawal due to the Buyer's fault, the Seller shall have the right to get the immediate return of the delivered products and to keep -as compensation for the use of the products by the Buyer- the installments already cashed and the down payment already received, except for the compensation of the further damage. The Buyer engages himself to fulfill all the necessary formalities, such as: registration of the confidential domain agreement in the register at the Court of the place where the products are, registration of the contract at the Registry office, where necessary, obligation not to transfer the products to a different place from the delivery place in order to make the property reserve in favor of the Seller enforceable towards Third Parties. Also, the Buyer engages himself not to sell the products, even temporarily, to Third Parties, not to rent them to Third Parties as well as not to transfer them without previous notice of the Seller.

Art. 8 - Claims and disputes.

8.1. Any claim or dispute concerning vices, discrepancies, defects, lack of product quality must be sent in writing to the Seller (by certified mail to bcs-pec@legalmail.it or by fax to the no. +39.02.94960800) within 15 days from the delivery of the product, i.e. when founding any vice, if any.

8.2. Any dispute concerning the execution of this contract cannot suspend any payment at all.

Art. 9 - Delays in payment.

9.1. In case of any payment delay in comparison with the agreed dates stated in the invoices, the Buyer will be automatically considered defaulted and the Seller will have the right to debit the interests for late payment at the rate foreseen in the Legislative Decree 192/2012 (BCE reference rate + 8% increase).

Art. 10 - Taxes, duties and other charges.

10.1. Any present or future charge including taxes, duties, stamps or other, are exclusively at the Buyer's charge.

Art. 11 - Processing of personal data.

11.1. On the ground of the Legislative Decree 30 June 2003 no. 196, the Buyer confirms that the "personal data" informed and/or exchanges also before the contract will be treated according to article 24, comma 1, letters b), c), d) of the Legislative Decree no. 196/2003 and further modifications and integrations. It is also understood that the Buyer expressly agrees to transfer the "personal data" on the ground of the article 42 and article 43 comma 1 letter a) of the Legislative Decree no. 196/2003 and however to notify and spread them on the ground of the article 25, comma 1 of the above Decree.

Art. 12 - Applicable law and competent court.

12.1. Any sale contract and the present commercial conditions are governed by the Italian Law.

12.2. Any dispute concerning the sale contracts will be governed by the Italian Jurisdiction and will be competence of the Court in Milan, exception made only for the Seller's right to mention the Buyer on the ground of the article 18 of the Code of Civil Procedure behind the Judge of the place where he lives or the registered office.



GENERAL TERMS AND CONDITIONS

CONDITIONS OF SUPPLY FOR MACHINES, IMPLEMENTS, ACCESSORIES AND SPARE PARTS

This Price List cancels and replaces any previous one.

This Price List can be modified at any time without previous notice.

The technical features and descriptions included in this Price List are given for information only and are not binding for BCS S.p.A.

BCS S.p.A. guarantees the safety requirements of the machines according to what prescribed by the regulations in force only if the machines are used according to what is indicated in the relevant instruction book. BCS S.p.A. declines any responsibility if any not foreseen implement and/or accessory is used, in case of tempering or misuse. BCS S.p.A. guarantees the safety requirements of the implements, accessories and spare parts according to what prescribed by the regulations in force only if the implements, accessories and spare parts are used according to what is indicated in the relevant instruction book, where foreseen BCS S.p.A. declines any responsibility in case of tempering or misuse.

The prices of the accessories without code relevant to tractors Price List are to be considered as "price surcharges" and therefore valid only if added to the configuration of the tractor. For any separate order of accessories, it is necessary to refer to the Commercial department.

For any tractor supplied without wheels, the relevant Declaration of Conformity will be issued only after a proper declaration proving the correct assembly of the homologated wheels according to the homologation requirements and the foreseen technical specifications. If it is necessary to assemble non-homologated wheels, this can be done after a written request of clearance to be sent to our Technical Dept. If approved, any cost arising from updating the registration certificate will be borne by the applicant.

For some spare parts, we will deliver a package. The quantity of the items included in each package is indicated in the reference column of the Spare parts Price List.

CONTENTS

TRACTOR RAPTOR DT	Page.
Tractor RAPTOR 40 DT	9
Price surcharge and accessories for RAPTOR DT	10-11
TRACTORS CROMO	
Tractors CROMO K30 and K40 AR	13
Price surcharge and accessories for CROMO K30 and K40 AR	14
Tractors CROMO K60 AR	15
Price surcharge and accessories for CROMO K60 AR	16-17-18
Tractors CROMO K30 and K40 RS	19
Price surcharge and accessories for CROMO K30 and K40 RS	20
Tractors CROMO K40 SDT RS (NEW)	21
Price surcharge and accessories for CROMO K40 SDT RS	22
Tractors CROMO K60 RS	23-24
Price surcharge and accessories for CROMO K60 RS	24-25-26-27
Tractors CROMO K60 MT	28
Price surcharge and accessories for CROMO K60 MT	29-30
TRACTORS COBRAM	
Tractors COBRAM 60 AR	32
Price surcharge and accessories for COBRAM 60 AR	33
Tractors COBRAM 60 RS	34
Price surcharge and accessories for COBRAM 60 RS	35-36

CONTENTS

TRACTORS THOR	Page
Tractors THOR L80 and K105 AR Tier 3B	38-39
Price surcharge and accessories for THOR L80 and K105 AR	40-41
Tractors THOR L80 and K105 RS Tier 3B	42-43
Price surcharge and accessories for THOR L80 and K105 RS	44-45
TRACTORS VEGA	
Tractors VEGA L80 and K105 SDT Tier 3B	47-48
Price surcharge and accessories for VEGA L80 and K105 SDT	49-50-51
Tractors VEGA L80 and K105 AR Tier 3B	52-53
Price surcharge and accessories for VEGA L80 and K105 AR	53-54-55-56
Tractors VEGA L80 and K105 RS Tier 3B	57-58
Price surcharge and accessories for VEGA L80 and K105 RS	58-59-60-61
Tractors VEGA L80 and K105 Dualsteer Tier 3B	62-63
Price surcharge and accessories for VEGA L80 and K105 Dualsteer	63-64-75-66
Tractors VEGA L80 and K105 MT Tier 3B	67-68
Price surcharge and accessories for VEGA K105 MT	68-69-70
Tractors VEGA SKY JUMP K105 Dualsteer Tier 3B	71-72
Price surcharge and accessories for VEGA SKY JUMP K105 Dualsteer	72-73
Engine specifications	74

Tractor RAPTOR DT

TRACTOR RAPTOR 40 DT

STANDARD MACHINE

- Synchronized gearbox: 24 speeds (12 FWD and 12 REV) with synchronized reverser
- Rear PTO 540 r.p.m., independent and synchronized with the gearbox
- Double-disc dry clutch, gearbox and PTO separately controlled
- 4-wheel drive with disengageable front axle
- Rear differential lock
- Oil-immersed multi-disc service brakes
- Parking brake acting on service brakes
- Hydrostatic steering
- Double-ram hydraulic lift with 3-point hitch cat. 1
- Hydraulic system **21,7 l/min** to feed steering device, lift and control valves
- **1 double acting control valve**
- Rear towing hook, with adjustable height
- Front towing hook
- 12V electric system with safety switch and socket, lighting system, stop and direction indicators
- Flash light setup
- Safety device to prevent accidental engine start
- Instrument panel with: motor revolution counter, work hours, motor water temperature and fuel level, PTO speed, warning lights
- Seat with spring suspension and safety belts
- Folding roll-bar, EC approved
- Wheels: 6.5/80-12 front, 250/80-18 rear, adjustable rim
- Complying with regulation 167/2013 EU (Mother Regulation)

RAPTOR 40 DT

4-CYLINDER ENGINE LOMBARDINI LDW 1404
25,5 KW / 35 HP - WATER COOLING

Euro

TS3N9182E

20.480

Price surcharge for non-standard wheels		Euro
*****	Front 23x8.50-12, rear 280/70-18 adjustable rim	210
*****	Garden front wheels 25x8.50-14, rear 36x13.50-15 fixed rim	1.660
*****	Front 7.00-12, rear 300/70-20 adjustable rim	310

Control valves for lift by rams (in addition to the standard ones)		
92481508	1 single acting and 1 double acting control valve with float (Required with front lift)	520
92481509	2 double acting control valves (1 with lever position for free return flow)	520

Control valves for lift with position and draft control (in addition to the standard ones)		
92481510	1 single acting control valve (Required with front lift)	210
92481511	1 double acting control valve with lever position for free return flow (With the hydraulic lift with position/draft control max 2 control valves can be fitted, the standard and the additional one)	210

Price surcharges non-standard accessories		
*****	Rear towing hook EC	240
*****	Kab Seating with springs	370
*****	Lift with position and draft control	900
*****	Steering wheel with adjustable height	170

Accessories		Euro
*****	Under-belly PTO at 2000 r.p.m. right (Splined shaft 1" 3/8) (Price surcharge)	210
*****	Front lift with front and under-belly PTO at 2000 r.p.m. right (Splined shaft 1" 3/8) (Price surcharge) (Must be combined with 1 single acting control valve) (Fitting of front weights not possible)	2.400
92480922	Adjustable rear working light kit	55
92481555	Flash light kit (for tractors without cabin)	100
92481330	Front weights 60 (Cannot be fitted on machines with front lift)	350
92481195	Weights for rear wheels Kg. 45 each (pair)	490

Tractors CROMO

TRACTORS CROMO K30 and K40 AR

STANDARD MACHINE

- With central articulation
- Gearbox with easy gear engagement: 8 forward and 4 reverse speeds
- Rear PTO 540 r.p.m., synchronized with the gearbox
- Single-disc dry clutch
- 4-wheel drive
- Front and rear differential lock
- Drum service brakes with mechanical control
- Parking brake acting on service brakes
- Hydrostatic steering acting on central articulated joint
- Double-ram hydraulic lift with 3-point hitch cat. 1
- Hydraulic system **16,5 l/min** to feed steering device, lift and control valves
- **1 hydraulic double acting control valve**
- Front and rear towing hook, with adjustable height
- 12V electric system with safety switch and socket, lighting system, stop and direction indicators
- Flash light setup
- Safety device to prevent accidental engine start
- Analogical instrument panel with: work hours, motor revolution counter, forward speed and warning lights
- Seat with spring suspension and safety belts
- Folding roll-bar, EC approved
- Wheels 6.50-16 adjustable rim
- Complying with regulation 167/2013 EU (Mother Regulation)

CROMO K30 AR

3-CYLINDER ENGINE KUBOTA D1105
18,6 KW / 25,2 HP - WATER COOLING

Euro

TOBBA183

16.750

CROMO K40 AR

4-CYLINDER ENGINE KUBOTA V1505
26,2 KW / 35,6 HP - WATER COOLING

Euro

TOCBB183

17.770

Price surcharge for non-standard wheels		Euro
*****	Wheels 210/95-16 adjustable rim	260
*****	Wheels 240/70-15 Garden fixed rim	1.040
*****	Wheels 260/70-16 adjustable rim	730
Control valves (in addition to the standard ones)		
92481751	1 single acting and 1 double acting control valve	600
92481752	1 double acting control valve and 1 with lever position for free return flow	630
Accessories		
*****	Rear towing hook EC (replacing the standard one)	240
92481763	Adjustable rear working light kit	55
92481555	Flash light kit	100
92481529	Weights for wheels 16" Kg. 40 each (pair)	400

TRACTORS CROMO K60 AR

STANDARD MACHINE

- With central articulation and **OS-FRAME**
- Synchronized gearbox: 24 speeds (12 FWD and 12 REV) with synchronized reverser
- Independent 2-speed rear PTO 540/540E r.p.m., with electro-hydraulically controlled wet multi-disc clutch and PTO synchronized with forward movement
- Oil-immersed multi-disc transmission clutch
- 4-wheel drive
- Front and rear differential lock, electro-hydraulically controlled
- Oil-immersed multi-disc service brakes
- Parking brake acting on service brakes
- Hydrostatic steering acting on central articulated joint
- Adjustable steering wheel
- Hydraulic lift by rams with 3-point hitch cat. 1
- Double-circuit hydraulic system with separate pumps
(lift and control valves **30,3 l/min** - hydroguide and controls **16,8 l/min**)
- **1 double acting hydraulic control valve without lockable delivery position** (version with lockable position not available)
- Front and rear towing hooks
- 12V electric system with safety switch and socket, lighting system, stop/direction indicators and rear working light
- Flash light setup
- Digital instrument panel with: work hours, motor water temperature and fuel level, simultaneous reading of motor revolutions, forward and PTO speed. Warning lights and sound signal
- Seat with spring suspension and safety belts
- Folding roll-bar, EC approved
- Wheels 8.25-16 adjustable rim
- Complying with regulation 167/2013 EU (Mother Regulation)

MONODIRECTIONAL

- Driving position with suspended platform
- 4-CYLINDER ENGINE - NATURALLY ASPIRATED
- KUBOTA V2203 - with counter-rotating balancing weights
- Direct injection – 35,2 KW / 48 HP - WATER COOLING

Euro

T0FBC210

29.150

REVERSIBLE VERSION

- Driving position with suspended platform on Silent Block device
- Reversible operator's position with rotating platform and twin pedals

4-CYLINDER ENGINE - NATURALLY ASPIRATED

KUBOTA V2203 - with counter-rotating balancing weights

Direct injection - 35,2 KW / 48 HP - WATER COOLING

Euro

T0GBC210	31.000
-----------------	---------------

Price surcharge for non-standard wheels

Euro

***** Wheels 250/80-18 adjustable rim	630
---------------------------------------	------------

***** Wheels 280/70-18 adjustable rim	730
---------------------------------------	------------

***** Wheels 320/65-18 adjustable rim	1.040
---------------------------------------	--------------

***** Wheels 260/70-20 adjustable rim	940
---------------------------------------	------------

***** Wheels 31x15.50-15 XTC fixed rim	830
--	------------

***** Wheels 31x15.50-15 STG fixed rim	830
--	------------

Control valves for lift by rams (in addition to the standard ones)

CROMO AR MONODIRECTIONAL WITHOUT CABIN

92481787	1 single acting and 1 double acting control valve with float	680
-----------------	--	------------

92481788	2 double acting control valves without lockable position (1 or 2 double acting hydraulic control valves with lockable position can be required)	680
-----------------	---	------------

CROMO AR MONODIRECTIONAL WITH CABIN

92481785	1 single acting and 1 double acting control valve with float	680
-----------------	--	------------

92481789	2 double acting control valves without lockable position (1 or 2 double acting hydraulic control valves with lockable position can be required)	680
-----------------	---	------------

CROMO AR REVERSIBLE WITH AND WITHOUT CABIN

92481794	1 single acting and 1 double acting control valve with float	680
-----------------	--	------------

92481795	2 double acting control valves without lockable position (1 or 2 double acting hydraulic control valves with lockable position can be required)	680
-----------------	---	------------

Control valves for lift with position and draft control (replacing the standard ones) for MONODIRECTIONAL and REVERSIBLE TRACTORS, WITH and WITHOUT cabin

92481778	1 single acting and 1 double acting control valve with float	210
-----------------	--	------------

Cabins

Lusso cabin, fully approved for safety and noise, with monocoque body fitted on silent-block device. Rear glass can be opened - rear window for passage of pipes. Glass doors with central plastic profile. Lower glass closing for optimum visibility of the ground from the front of the cabin. Ventilation and heating system with easily accessible dust filter, removable and replaceable without tools. Quick couplers for heating disconnection. Rear and front windscreen wipers and washers. Fixed front working lights, moveable rear working lights. Rear view mirrors. Flashing light. Porthole on rear side of sun roof. Fabric covered seat instead of standard one.

	For monodirectional version	6.240
--	------------------------------------	--------------

	For reversible version	5.720
--	-------------------------------	--------------

Comfort cabin, fully approved for safety and noise, with monocoque body fitted on silent-block device. Rear glass can be opened - rear window for passage of pipes. Glass doors with central plastic profile. Lower glass closing for optimum visibility of the ground from the front of the cabin. Ventilation and heating system with easily accessible dust filter, removable and replaceable without tools. Quick couplers for heating disconnection. Rear and front windscreen wipers and washers. Fixed front working lights, moveable rear working lights. Rear view mirrors. Flashing light. Porthole on rear side of sun roof. Air conditioning with evaporator in sun roof. Fabric covered seat instead of standard one.

	For monodirectional version	8.640
--	------------------------------------	--------------

	For reversible version	8.120
--	-------------------------------	--------------

92481694 Active carbon filter for cabin **100**

Price surcharge for non-standard accessories		Euro
*****	Third point with quick couplings, L-shaped, cat. 1 - Arms with adjustable length and hooks with adjustable width	980
*****	Rear towing hook EC	240
*****	Rear towing hook EC with Slider frame	520
*****	Rear towing hook CUNA with Slider frame	520
*****	Kab Seating	390
*****	Lift with position and draft control (Two double acting control valves without lockable position are provided) (1 or 2 double acting control valves with lockable position can be required)	1.120
*****	Oversized pump replacing the standard ones and heat exchanger (lift and control valves 33,2 l/min - hydroguide and controls 20,7 l/min) (Standard with joystick)	370
*****	Electronic joystick including 1 single acting control valve with adjustable flow and free return, 3 double acting control valves (replacing the standard ones), oversized pumps and heat exchanger	
	For monodirectional version	5.200
	For reversible version	4.580
(The joystick cannot be used with the hydraulic lift with position/draft control and the Kab Seating)		

Accessories

92481555	Flash light kit (for tractors without cabin)	100
92481195	Weights for wheels 18" Kg. 45 each (pair)	490
92481933	Front weights Kg. 100 for tractors with and without cabin	680

Front weights can be mounted on both sides of the engine

TRACTORS CROMO K30 and K40 RS

STANDARD MACHINE

- Rigid, front steering wheels
- Gearbox with easy gear engagement: 8 forward and 4 reverse speeds
- Rear PTO 540 r.p.m., synchronized with the gearbox
- Single-disc dry clutch
- 4-wheel drive
- Rear and front differential lock
- Drum service brakes with mechanical control
- Parking brake acting on service brakes
- Hydrostatic steering
- Double-ram hydraulic lift with 3-point hitch cat. 1
- Hydraulic system **16,5 l/min** to feed steering device, lift and control valves
- **1 hydraulic double acting control valve**
- Front and rear towing hook, with adjustable height
- 12V electric system with safety switch and socket, lighting system, stop and direction indicators
- Flash light setup
- Safety device to prevent accidental engine start
- Analogical instrument panel with: work hours, motor revolution counter, forward speed and warning lights
- Seat with spring suspension and safety belts
- Folding roll-bar, EC approved
- Wheels 6.50-16 adjustable rim
- Complying with regulation 167/2013 EU (Mother Regulation)

CROMO K30 RS

3-CYLINDER ENGINE KUBOTA D1105
18,6 KW / 25,2 HP - WATER COOLING

Euro

T0DBA183

17.060

CROMO K40 RS

4-CYLINDER ENGINE KUBOTA V1505
26,2 KW / 35,6 HP - WATER COOLING

Euro

T0EBB183

18.080

Price surcharge for non-standard wheels		Euro
*****	Wheels 210/95-16 adjustable rim	260
*****	Wheels 240/70-15 Garden fixed rim	1.040
*****	Wheels 260/70-16 adjustable rim	730

Control valves (in addition to the standard ones)		
92481748	1 single acting control valve	200
92481749	1 double acting control valve	200
92481750	1 double acting control valve with float	240

On CROMO RS tractors max 2 control valves can be fitted, the standard and the additional one

Price surcharge for non-standard accessories		
*****	Independent rear power take-off at 540 r.p.m. with electro-hydraulically controlled wet multidisc clutch and PTO synchronized with forward movement. For CROMO K40 RS only	1.120

Accessories		
*****	Rear towing hook EC (replacing the standard one)	240
92481763	Adjustable rear working light kit	55
92481555	Flash light kit	100
92481529	Weights for rear wheels 16" Kg. 40 each (pair)	400
92481768	Weights for front wheels 16" Kg. 40 each (pair) with connections	430

TRATTORE CROMO K40 SDT RS (NEW)

STANDARD MACHINE

- Rigid, front steering wheels
- Gearbox with easy gear engagement: 8 forward and 4 reverse speeds
- Rear PTO 540 r.p.m., synchronized with the gearbox
- Single-disc dry clutch
- 4-wheel drive
- Rear and front differential lock
- Drum service brakes with mechanical control
- Parking brake acting on service brakes
- Hydrostatic steering
- Double-ram hydraulic lift with 3-point hitch cat. 1
- Hydraulic system **16,5 l/min** to feed steering device, lift and control valves
- **1 hydraulic double acting control valve**
- Front and rear towing hook, with adjustable height
- 12V electric system with safety switch and socket, lighting system, stop and direction indicators
- Flash light setup
- Safety device to prevent accidental engine start
- Analogical instrument panel with: work hours, motor revolution counter, forward speed and warning lights
- Seat with spring suspension and safety belts
- Folding roll-bar, EC approved
- Wheels 6.00-16 * 8.25-16 adjustable rim
- Complying with regulation 167/2013 EU (Mother Regulation)

CROMO K40 SDT RS

4-CYLINDER ENGINE KUBOTA V1505
26,2 KW / 35,6 HP - WATER COOLING

Euro

TB8BB183

18.580

Price surcharge for non-standard wheels	Euro
---	------

***** Wheels 6.50-16 * 280/70-18 adjustable rim	520
---	-----

Control valves (in addition to the standard ones)	
---	--

92481748 1 single acting control valve	200
--	-----

92481749 1 double acting control valve	200
--	-----

92481750 1 double acting control valve with float	240
---	-----

On CROMO K40 SDT RS tractors max 2 control valves can be fitted, the standard and the additional one

Price surcharge for non-standard accessories	
--	--

***** Independent rear power take-off at 540 r.p.m. with electro-hydraulically controlled wet multidisc clutch and PTO synchronized with forward movement.	1.120
--	-------

Accessories	
-------------	--

***** Rear towing hook EC (replacing the standard one)	240
---	-----

***** Kab Seating	320
-------------------	-----

***** Steering wheel with adjustable height	110
---	-----

92481763 Adjustable rear working light kit	55
--	----

92481555 Flash light kit	100
--------------------------	-----

92481529 Weights for rear wheels 16" Kg. 40 each (pair)	400
---	-----

92481768 Weights for front wheels 16" Kg. 40 each (pair) with connections	430
---	-----

92481975 Weights for rear wheels 18" Kg. 45 each (pair) with connections	520
--	-----

TRACTORS CROMO K60 RS

STANDARD MACHINE

- Rigid, front steering wheels and **OS-FRAME**
- Synchronized gearbox: 24 speeds (12 FWD and 12 REV) with synchronized reverser
- Independent 2-speed rear PTO 540/540E r.p.m., with electro-hydraulically controlled wet multi-disc clutch and PTO synchronized with forward movement
- Oil-immersed multi-disc transmission clutch
- 4-wheel drive
- Front and rear differential lock , electro-hydraulically controlled
- Oil-immersed multi-disc service brakes
- Parking brake acting on service brakes
- Hydrostatic steering
- Adjustable steering wheel
- Hydraulic lift by rams with 3-point hitch cat. 1
- Double-circuit hydraulic system with separate pumps
(lift and control valves **30,3 l/min** - hydroguide and controls **16,8 l/min**)
- **1 double acting hydraulic control valve without lockable delivery position** (version with lockable position not available)
- Front and rear towing hooks
- 12V electric system with safety switch and socket, lighting system, stop/direction indicators and rear working light
- Flash light setup
- Digital instrument panel with: work hours, motor water temperature and fuel level, simultaneous reading of motor revolutions, forward and PTO speed. Warning lights and sound signal
- Seating with spring suspension and safety belts
- Folding roll-bar, EC approved
- Wheels 8.25-16 adjustable rim
- Compliant with regulation 167/2013 EU (Mother Regulation)

MONODIRECTIONAL

- Driving position with suspended platform
- 4-CYLINDER ENGINE - NATURALLY ASPIRATED
 KUBOTA V2203 - with counter-rotating balancing weights
 Direct injection – 35,2 KW / 48 HP - WATER COOLING

Euro

TOHBC210

29.570

REVERSIBLE VERSION

- Driving position with suspended platform on Silent Block device
- Reversible operator's position with rotating platform and twin pedals

4-CYLINDER ENGINE - NATURALLY ASPIRATED

KUBOTA V2203 - with counter-rotating balancing weights

Direct injection – 35,2 KW / 48 HP - WATER COOLING

Euro

T0IBC210	31.420
-----------------	---------------

Price surcharge for non-standard wheels	Euro
--	-------------

*****	Wheels 250/80-18 adjustable rim	630
*****	Wheels 280/70-18 adjustable rim	730
*****	Wheels 320/65-18 adjustable rim	1.040
*****	Wheels 260/70-20 adjustable rim	940
*****	Wheels 31x15.50-15 XTC fixed rim	830
*****	Wheels 31x15.50-15 STG fixed rim	830

Control valves for lift by rams (in addition to the standard ones)

CROMO RS MONODIRECTIONAL WITHOUT CABIN

92481792	1 single acting and 1 double acting control valve with float	680
92481700	2 double acting control valves without lockable position (1 or 2 double acting hydraulic control valves with lockable position can be required)	680

CROMO RS MONODIRECTIONAL WITH CABIN

92481790	1 single acting and 1 double acting control valve with float	680
92481701	2 double acting control valves without lockable position (1 or 2 double acting hydraulic control valves with lockable position can be required)	680

CROMO RS REVERSIBLE WITH AND WITHOUT CABIN

92481791	1 single acting and 1 double acting control valve with float	680
92481782	2 double acting control valves without lockable position (1 or 2 double acting hydraulic control valves with lockable position can be required)	680

Control valves for lift with position and draft control (replacing the standard ones) for MONODIRECTIONAL and REVERSIBLE TRACTORS, WITH and WITHOUT cabin

92481778	1 single acting and 1 double acting control valve with float	210
----------	--	-----

Accumulator for weight compensation

*****	Accumulator for weight compensation HDR with DUAL FLOATING SYSTEM ONLY FOR REVERSIBLE VERSION including 1 single acting control valve and 1 double acting control valve with float	1.420
-------	---	-------

*****	Accumulator for weight compensation HDR with DUAL FLOATING SYSTEM ONLY FOR REVERSIBLE VERSION including 2 double acting control valves without lockable position	1.420
-------	---	-------

(The accumulator for weight compensation cannot be used with the hydraulic lift with position/draft control and the joystick. Standard control valve non included)

Cabins

***** **Lusso** cabin, fully approved for safety and noise, with monocoque body fitted on silent-block device. Rear glass can be opened - rear window for passage of pipes. Glass doors with central plastic profile. Lower glass closing for optimum visibility of the ground from the front of the cabin. Ventilation and heating system with easily accesible dust filter, removable and replaceable without tools. Quick couplers for heating disconnection. Rear and front windscreen wipers and washers. Fixed front working lights, moveable rear working lights. Rear view mirrors. Flashing light. Porthole on rear side of sun roof. Fabric covered seat instead of standard one.

	For monodirectional version	6.240
--	------------------------------------	--------------

	For reversible version	5.720
--	-------------------------------	--------------

***** **Comfort** cabin, fully approved for safety and noise, with monocoque body fitted on silent-block device. Rear glass can be opened - rear window for passage of pipes. Glass doors with central plastic profile. Lower glass closing for optimum visibility of the ground from the front of the cabin. Ventilation and heating system with easily accessible dust filter, removable and replaceable without tools. Quick couplers for heating disconnection. Rear and front windscreen wipers and washers. Fixed front working lights, moveable rear working lights. Rear view mirrors. Flashing light. Porthole on rear side of sun roof. Air conditioning with evaporator in sun roof. Fabric covered seat instead of standard one.

For monodirectional version	8.640
------------------------------------	--------------

For reversible version	8.120
-------------------------------	--------------

92481694	Active carbon filter for cabin	100
-----------------	--------------------------------	------------

Price surcharge for non-standard accessories

*****	Third point with quick couplings cat. 1 - Arms without adjustable length	420
-------	--	------------

*****	Third point with quick couplings, L-shaped, cat. 1 - Arms with adjustable length and hooks with adjustable width	980
-------	--	------------

*****	Rear towing hook EC	240
-------	----------------------------	------------

*****	Rear towing hook EC with Slider frame	520
-------	--	------------

*****	Rear towing hook CUNA with Slider frame	520
-------	--	------------

*****	Kab Seating	390
-------	-------------	------------

*****	Lift with position and draft control (Two double acting control valves without lockable position are provided) (1 or 2 double acting control valves with lockable position can be required)	1.120
-------	--	--------------

*****	Oversized pump replacing the standard ones and heat exchanger (lift and control valves 33,2 l/min - hydroguide and controls 20,7 l/min) (Standard with joystick)	370
*****	Electronic joystick including 1 single acting control valve with adjustable flow and free return, 3 double acting control valves (replacing the standard ones), oversized pumps and heat exchanger	
	For monodirectional version	5.200
	For reversible version	4.580
	(The joystick cannot be used with the hydraulic lift with position/draft control, the Kab Seating and the hydraulic suspension)	

Accessories		
92481555	Flash light kit (for tractors without cabin)	100
92481195	Weights for wheels 18" Kg. 45 each (pair)	490
92481933	Front weights Kg. 100 for tractors with and without cabin	680

Front weights can be mounted on both sides of the engine



TRACTORS CROMO K60 MT REVERSIBLE

STANDARD MACHINE

- Rigid, front steering wheels and **OS-FRAME – Haymaking version**
- Synchronized gearbox: 24 speeds (12 FWD and 12 REV) with synchronized reverser
- Independent 2-speed rear PTO 540/540E r.p.m., with electro-hydraulically controlled wet multi-disc clutch and PTO synchronized with forward movement
- Oil-immersed multi-disc transmission clutch
- 4-wheel drive
- Front and rear differential lock, electro-hydraulically controlled
- Oil-immersed multi-disc service brakes
- Parking brake acting on service brakes
- Driving position with platform suspended on silent-block device
- Reversible operator's position with rotating platform and twin pedals
- Hydrostatic steering
- Adjustable steering wheel
- Hydraulic lift by rams with 3-point hitch cat. 1
- Double-circuit hydraulic system with separate pumps
(lift and control valves **30,3 l/min** - hydroguide and controls **16,8 l/min**)
- **Control valves: 1 single acting and 1 double acting with float**
- **Hydraulic suspension HDR with Dual Floating system**
- Front and rear towing hooks
- 12V electric system with safety switch and socket, lighting system, stop/direction indicators and flash light
- Digital instrument panel with: work hours, motor water temperature and fuel level, simultaneous reading of motor revolutions, forward and PTO speed. Warning lights and sound signal
- Seat with spring suspension and safety belts
- Semi-cabin with roll over protection and headlights, rear view mirrors, front and rear windscreen wipers
- Wheels 31x15.50-15 XTC fixed rim
- Complying with regulation 167/2013 EU (Mother Regulation)

CROMO K60 MT

4-CYLINDER ENGINE - NATURALLY ASPIRATED
KUBOTA V2203 - with counter-rotating balancing weights
Direct injection – 35,2 KW / 48 HP - WATER COOLING

Euro

T0JBC110V

37.080

Price surcharge for non-standard wheels		Euro
*****	Wheels 31x15.50-15 STG fixed rim	no price surcharge
*****	Wheels 33x15.50-15 XTC fixed rim	210
Control valves (replacing the standard ones)		
92481796	2 double acting control valves without lockable position (1 or 2 double acting hydraulic control valves with lockable position can be required)	110
Cabins		
*****	Lusso cabin, fully approved for safety and noise, with monocoque body fitted on silent-block device. Rear glass can be opened - rear window for passage of pipes. Glass doors with central plastic profile. Lower glass closing for optimum visibility of the ground from the front of the cabin. Ventilation and heating system with easily accesible dust filter, removable and replaceable without tools. Quick couplers for heating disconnection. Rear and front windscreen wipers and washers. Fixed front working lights, moveable rear working lights. Rear view mirrors. Flashing light. Porthole on rear side of sun roof. Fabric covered seat instead of standard one.	2.400
*****	Comfort cabin, fully approved for safety and noise, with monocoque body fitted on silent-block device. Rear glass can be opened - rear window for passage of pipes. Glass doors with central plastic profile. Lower glass closing for optimum visibility of the ground from the front of the cabin. Ventilation and heating system with easily accesible dust filter, removable and replaceable without tools. Quick couplers for heating disconnection. Rear and front windscreen wipers and washers. Fixed front working lights, moveable rear working lights. Rear view mirrors. Flashing light. Porthole on rear side of sun roof. Air conditioning with evaporator in sun roof. Fabric covered seat instead of standard one.	4.800
92481694	Active carbon filter for cabin	100

Price surcharge for non-standard accessories

*****	Third point with quick couplings cat. 1 - Arms without adjustable length	420
*****	Third point with quick couplings, L-shaped, cat. 1 - Arms with adjustable length and hooks with adjustable width	980
*****	Rear towing hook EC	240
*****	Rear towing hook EC with Slider frame	520
*****	Rear towing hook CUNA with Slider frame	520
*****	Oversized pump replacing the standard ones and heat exchanger (lift and control valves 33,2 l/min - hydroguide and controls 20,7 l/min)	370

Accessories

92481933	Front weights Kg. 100 for tractors with and without cabin	680
-----------------	---	------------

Front weights can be mounted on both sides of the engine

Tractors COBRAM

TRACTORS COBRAM 60 AR

STANDARD MACHINE

- With central articulation and **OS-FRAME**
- Synchronized gearbox: 24 speeds (12 FWD and 12 REV) with synchronized reverser
- Independent rear PTO at 540 r.p.m., with electro-hydraulically controlled wet multi-disc clutch and PTO synchronized with forward movement
- Oil-immersed multi-disc transmission clutch
- 4-wheel drive
- Front and rear differential lock, electro-hydraulically controlled
- Oil-immersed multi-disc service brakes
- Parking brake acting on service brakes
- Hydrostatic steering acting on central articulated joint
- Adjustable steering wheel
- Hydraulic lift by rams with 3-point hitch cat. 1
- Double-circuit hydraulic system with separate pumps (lift and control valves **25,6 l/min** - hydroguide and controls **15,4 l/min**)
- **1 double acting hydraulic control valve without lockable delivery position** (version with lockable position not available)
- Front and rear towing hooks
- 12V electric system with safety switch and socket, lighting system, stop/direction indicators and rear working light
- Flash light setup
- Digital instrument panel with: work hours, motor water temperature and fuel level, simultaneous reading of motor revolutions, forward and PTO speed. Warning lights and sound signal
- Seat with spring suspension and safety belts
- Folding roll-bar, EC approved
- Wheels 8.25-16 adjustable rim
- Complying with regulation 167/2013 EU (Mother Regulation)

MONODIRECTIONAL

4-CYLINDER ENGINE KOHLER KDi 2504 M - with counter-rotating balancing weights
Direct injection 36 KW / 49 HP - WATER COOLING

Euro

T0KBD210

27.510

REVERSIBLE VERSION

• Reversible operator's position with rotating platform and twin pedals
4-CYLINDER ENGINE KOHLER KDi 2504 M - with counter-rotating balancing weights
Direct injection 36 KW / 49 HP - WATER COOLING

Euro

T0LBD210

28.650

Price surcharge for non-standard wheels		Euro
*****	Wheels 250/80-18 adjustable rim	630
*****	Wheels 280/70-18 adjustable rim	730
*****	Wheels 320/65-18 adjustable rim	1.040
*****	Wheels 260/70-20 adjustable rim	940
*****	Wheels 31x15.50-15 XTC fixed rim	830
*****	Wheels 31x15.50-15 STG fixed rim	830
Control valves for lift by rams (in addition to the standard ones)		
92481783	1 single acting and 1 double acting control valve with float	580
92481784	2 double acting control valves without lockable position (1 or 2 double acting hydraulic control valves with lockable position can be required)	580
Control valves for lift with position and draft control (replacing the standard ones)		
92481781	1 single acting control valve and 1 double acting control valve with float	260
Price surcharge for non-standard accessories		
*****	Third point with quick couplings, L-shaped, cat. 1 - Arms with adjustable length and hooks with adjustable width	980
*****	Rear towing hook EC	240
*****	Lift with position and draft control (Two double acting control valves without lockable position are provided) (1 or 2 double acting control valves with lockable position can be required)	1.040
Accessories		
92481555	Flash light kit (for tractors without cabin)	100
92481195	Weights for wheels 16", 18" and 20" Kg. 45 each (pair)	490
92481934	Front weights Kg. 100	680
Front weights can be mounted on both sides of the engine		



TRACTORS COBRAM 60 RS

STANDARD MACHINE

- Rigid, front steering wheels and **OS-FRAME**
- Synchronized gearbox: 24 speeds (12 FWD and 12 REV) with synchronized reverser
- Independent rear PTO at 540 r.p.m., with electro-hydraulically controlled wet multi-disc clutch and PTO synchronized with forward movement
- Oil-immersed multi-disc transmission clutch
- 4-wheel drive
- Front and rear differential lock, electro-hydraulically controlled
- Oil-immersed multi-disc service brakes
- Parking brake acting on service brakes
- Hydrostatic steering acting on front wheels
- Adjustable steering wheel
- Hydraulic lift by rams with 3-point hitch cat. 1
- Double-circuit hydraulic system with separate pumps (lift and control valves **25,6 l/min** - hydroguide and controls **15,4 l/min**)
- **1 double acting hydraulic control valve without lockable delivery position** (version with lockable position not available)
- Front and rear towing hooks
- 12V electric system with safety switch and socket, lighting system, stop/direction indicators and rear working light
- Flash light setup
- Digital instrument panel with: work hours, motor water temperature and fuel level, simultaneous reading of motor revolutions, forward and PTO speed. Warning lights and sound signal
- Seat with spring suspension and safety belts
- Folding roll-bar, EC approved
- Wheels 8.25-16 adjustable rim
- Complying with regulation 167/2013 EU (Mother Regulation)

MONODIRECTIONAL

4-CYLINDER ENGINE KOHLER KDi 2504 M - with counter-rotating balancing weights
Direct injection 36 KW / 49 HP - WATER COOLING

Euro

T0MBD210

27.810

REVERSIBLE VERSION

• Reversible operator's position with rotating platform and twin pedals
4-CYLINDER ENGINE KOHLER KDi 2504 M - with counter-rotating balancing weights
Direct injection 36 KW / 49 HP - WATER COOLING

Euro

T0NBD210

28.950

Price surcharge for non-standard wheels		Euro
*****	Wheels 250/80-18 adjustable rim	630
*****	Wheels 280/70-18 adjustable rim	730
*****	Wheels 320/65-18 adjustable rim	1.040
*****	Wheels 260/70-20 adjustable rim	940
*****	Wheels 31x15.50-15 XTC fixed rim	830
*****	Wheels 31x15.50-15 STG fixed rim	830

Control valves for lift by rams (in addition to the standard ones)		
92481486	1 single acting and 1 double acting control valve with float	370
92481786	2 double acting control valves without lockable position (1 or 2 double acting hydraulic control valves with lockable position can be required)	370

Control valves for lift with position and draft control (replacing the standard ones)		
92481781	1 single acting control valve and 1 double acting control valve with float	260

REVERSIBLE VERSION ONLY

*****	Accumulator for weight compensation HDR with including 1 flow regulator, 1 double acting control valve with float and 1 double acting control valve with 4 fixed positions (The accumulator for weight compensation cannot be used with the hydraulic lift with position/draft control. Standard control valve non included)	1.150
-------	---	-------

Price surcharge for non-standard accessories

*****	Third point with quick couplings cat. 1 - Arms without adjustable length	520
*****	Third point with quick couplings, L-shaped, cat. 1 - Arms with adjustable length and hooks with adjustable width	980
*****	Rear towing hook EC	240
*****	Lift with position and draft control (Two double acting control valves without lockable position are provided) (1 or 2 double acting hydraulic control valves with lockable position can be required) (Cannot be used with the accumulator for weight compensation)	1.040

Accessories

92481555	Flash light kit	100
92481195	Weights for wheels 16", 18" and 20" Kg. 45 each (pair)	490
92481934	Front weights Kg.100	680

Front weights can be mounted on both sides of the engine

Tractors THOR

TRACTORS THOR L80 and K105 AR TIER 3B

STANDARD MACHINE

- With central articulation and **OS-FRAME**
- Synchronized gearbox: 32 speeds (16 FWD and 16 REV) with synchronized reverser
- Independent 2-speed rear PTO 540/540E r.p.m., with electro-hydraulically controlled wet multi-disc clutch and PTO synchronized with forward movement
- Flywheel with long-travel torsional damper
- Oil-immersed multi-disc transmission clutch
- 4-wheel drive
- Front and rear differential lock , electro-hydraulically controlled
- Oil-immersed multi-disc service brakes
- Parking brake acting on service brakes
- Power steering with dual-rams acting on central articulated joint
- Steering wheel with adjustable height
- Double-circuit hydraulic system with separate pumps and heat exchanger
K105: lift and control valves **27,7 l/min** - hydroguide and controls **33,1 l/min**
L80 : lift and control valves **29,5 l/min** - hydroguide and controls **33,5 l/min**
- Rear hydraulic lift by rams with ordinary hitches cat. 1 and 2 - Lifting capacity 2300 kg
- **1 single acting control valve and 2 double acting control valves without lockable delivery position** (1 or 2 double acting hydraulic control valves with lockable position can be required)
- Protection for engine oil pan
- Front and rear towing hooks
- 12V electric system with safety switch, lighting system, stop/direction indicators and rear working light
- Flash light setup
- Digital instrument panel with multi-function colour display and hour counter, battery and consumption level, **Diesel Particulate Filter level (K105)**, simultaneous reading of motor revolutions, forward and PTO speed. Warning lights and sound signal.
- Adjustable seat with spring suspension and safety belts
- Integrated cyclone prefilter with high-performance air filter and front air intake
- Folding roll-bar, EC approved
- Wheels 250/80-18 adjustable rim
- EC type approved to 40 km/h
- Complying with regulation 167/2013 EU (Mother Regulation)

THOR L80 AR MONODIRECTIONAL

4-CYLINDER ENGINE TURBO INTERCOOLER KOHLER KDI 2504 TCR
Direct injection - with counter-rotating balancing weights
55,4 KW / 75,3 HP WATER COOLING

Euro

TA2AZ110

45.840

THOR L80 AR REVERSIBLE

• Reversible operator's position with rotating platform and twin pedals
4-CYLINDER ENGINE TURBO INTERCOOLER KOHLER KDI 2504 TCR
Direct injection - with counter-rotating balancing weights
55,4 KW / 75,3 HP WATER COOLING

Euro

TA3AZ110

47.490

THOR K105 AR MONODIRECTIONAL

4-CYLINDER ENGINE TURBO KUBOTA V3800 CR-T-E4B
Direct injection - with counter-rotating balancing weights
72,1 KW / 98 HP WATER COOLING

Euro

TORBE110

50.060

THOR K105 AR REVERSIBLE

• Reversible operator's position with rotating platform and twin pedals
4-CYLINDER ENGINE TURBO KUBOTA V3800 CR-T-E4B
Direct injection - with counter-rotating balancing weights
72,1 KW / 98 HP WATER COOLING

Euro

TOSBE110

51.710

Price surcharge for non-standard wheels		Euro
*****	Wheels 11.5/80-15.3 fixed rim	110
*****	Wheels 280/70-18 adjustable rim	370
*****	Wheels 320/65-18 adjustable rim	680
*****	Wheels 9.50-20 (250/85-20) adjustable rim	370
*****	Wheels 300/70-20 adjustable rim	890
*****	Wheels 340/65-20 adjustable rim	1.300
*****	Wheels Terra-Tyre 31x15.50-15 XTC fixed rim	580
*****	Wheels Terra-Tyre 31x15.50-15 STG fixed rim	580

Control valves for lift by rams (replacing the standard ones)		
92481821	1 single acting control valve, 1 double acting control valve without lockable position, 1 double acting control valve with float (A double acting control valve with lockable position can be required)	140
92481822	3 double acting control valves without lockable position (1 or 2 double acting hydraulic control valves with lockable position can be required)	140

Control valves for lift with position and draft control (replacing the standard ones)		
92481823	1 single acting and 1 double acting control valve without lockable position (A double acting control valve with lockable position can be required)	140
92481824	1 double acting control valve without lockable position and 1 double acting control valve with float (A double acting control valve with lockable position can be required)	140

Price surcharge for non-standard accessories

*****	Third point with quick couplings, L-shaped, cat. 1 and 2 - Arms with adjustable length and hooks with adjustable width	730
*****	Towing hook EC	230
*****	Towing hook EC with Slider frame	520
*****	Towing hook CUNA with Slider frame	520
*****	Hydraulic lift strut and tie system	500
*****	Kab Seating	330
*****	Lift with position and draft control (Two double acting control valves without lockable position are provided) (1 or 2 double acting hydraulic control valves with lockable position can be required)	630

Accessories

*****	Front lift with front protection and 2 double acting control valves (Must be combined with 1 single acting control valve) (Cannot be used with front weights and bumper)	3.070
*****	Oversized pump (replacing the standard one) to lift and control valves: 48,8 lt/min (K105) - 51 lt/min (L80)	160
92481555	Flash light kit	100
92481829	Front weights Kg. 120 (Cannot be fitted on machines with front lift) Front weights can be mounted on both sides of the engine	940
92481930	Front bumper (Cannot be fitted on machines with front lift)	730
92480923	Weights for wheels 18" - 20" Kg. 50 each (pair)	680

TRACTORS THOR L80 and K105 RS TIER 3B

STANDARD MACHINE

- Rigid, front steering wheels and **OS-FRAME**
- Synchronized gearbox: 32 speeds (16 FWD and 16 REV) with synchronized reverser
- Independent 2-speed rear PTO 540/540E r.p.m., with electro-hydraulically controlled wet multi-disc clutch and PTO synchronized with forward movement
- Flywheel with long-travel torsional damper
- Oil-immersed multi-disc transmission clutch
- 4-wheel drive
- Front and rear differential lock , electro-hydraulically controlled
- Oil-immersed multi-disc service brakes
- Parking brake acting on service brakes
- Power steering with dual-rams acting on front wheels
- Steering wheel with adjustable height
- Double-circuit hydraulic system with separate pumps and heat exchanger
K105: lift and control valves **27,7 l/min** - hydroguide and controls **33,1 l/min**
L80 : lift and control valves **29,5 l/min** - hydroguide and controls **33,5 l/min**
- Rear hydraulic lift by rams with ordinary hitches cat. 1 and 2 - Lifting capacity 2300 kg
- **1 single acting control valve and 2 double acting control valves without lockable delivery position** (1 or 2 double acting hydraulic control valves with lockable position can be required)
- Protection for engine oil pan
- Front and rear towing hooks
- 12V electric system with safety switch, lighting system, stop and direction indicators
- Ready to fit flash and rear working light
- Digital instrument panel with multi-function colour display and hour counter, battery and consumption level, **Diesel Particulate Filter level (K105)**, simultaneous reading of motor revolutions, forward and PTO speed. Warning lights and sound signal.
- Adjustable seat with spring suspension and safety belts
- Integrated cyclone prefilter with high-performance air filter and front air intake
- Folding roll-bar, EC approved
- Wheels 280/80-18 adjustable rim
- EC type approved to 40 km/h
- Complying with regulation 167/2013 EU (Mother Regulation)

THOR L80 RS MONODIRECTIONAL

4-CYLINDER ENGINE TURBO INTERCOOLER KOHLER KDI 2504 TCR
Direct injection - with counter-rotating balancing weights
55,4 KW / 75,3 HP WATER COOLING

Euro

TA4AZA10

46.560

THOR L80 RS REVERSIBLE

• Reversible operator's position with rotating platform and twin pedals
4-CYLINDER ENGINE TURBO INTERCOOLER KOHLER KDI 2504 TCR
Direct injection - with counter-rotating balancing weights
55,4 KW / 75,3 HP WATER COOLING

Euro

TA5AZA10

48.210

THOR K105 RS MONODIRECTIONAL

4-CYLINDER ENGINE TURBO KUBOTA V3800 CR-T-E4B
Direct injection - with counter-rotating balancing weights
72,1 KW / 98 HP WATER COOLING

Euro

TOTBEA10

50.780

THOR K105 RS REVERSIBLE

• Reversible operator's position with rotating platform and twin pedals
4-CYLINDER ENGINE TURBO KUBOTA V3800 CR-T-E4B
Direct injection - with counter-rotating balancing weights
72,1 KW / 98 HP WATER COOLING

Euro

TOUBEA10

52.430

Price surcharge for non-standard wheels		Euro
*****	Wheels 9.50-20 (250/85-20) adjustable rim	no price surcharge
*****	Wheels 320/65-18 adjustable rim	310
*****	Wheels 340/65-18 adjustable rim	2.080
*****	Wheels 300/70-20 adjustable rim	520
*****	Wheels 320/70-20 adjustable rim	670
*****	Wheels 340/65-20 adjustable rim	930
*****	Wheels Terra-Tyre 31x15.50-15 XTC fixed rim	210
*****	Wheels Terra-Tyre 31x15.50-15 STG fixed rim	210
*****	Wheels 13.6-16 Garden fixed rim	1.970

Control valves for lift by rams (replacing the standard ones)		
92481825	1 single acting control valve, 1 double acting control valve without lockable position, 1 double acting control valve with float (A double acting control valve with lockable position can be required)	140
92481826	3 double acting control valves without lockable position (1 or 2 double acting control valves with lockable position can be required)	140

Control valves for lift with position and draft control (replacing the standard ones)		
92481828	1 single acting control valve, 1 double acting control valve without lockable position, 1 double acting control valve with float (A double acting control valve with lockable position can be required)	140
92481827	3 double acting control valves without lockable position (1 or 2 double acting control valves with lockable position can be required)	140

Price surcharge for non-standard accessories

*****	Third point with quick couplings cat. 1 and 2 - Arms with adjustable length	390
*****	Third point with quick couplings, L-shaped, cat. 1 and 2 - Arms with adjustable length and hooks with adjustable width	730
*****	Towing hook EC	230
*****	Towing hook EC with Slider frame	520
*****	Towing hook CUNA with Slider frame	520
*****	Hydraulic lift strut and tie system	500
*****	Kab Seating	330
*****	Lift with position and draft control (Two double acting control valves without lockable position are provided) (1 or 2 double acting hydraulic control valves with lockable position can be required) (Cannot be used with the accumulator for weight compensation)	970
*****	Accumulator for weight compensation HDR including 1 flow regulator, 1 double acting control valve with float and 1 double acting control valve with 4 fixed positions (Control valves replacing the standard ones) (The accumulator for weight compensation cannot be used with the hydraulic lift with position/draft control)	840

Accessories

*****	Front lift with front protection and 2 double acting control valves (Must be combined with 1 single acting control valve) (Cannot be used with front weights and bumper)	3.070
*****	Oversized pump (replacing the standard one) to lift and control valves: 48,8 lt/min (K105) - 51 lt/min (L80)	160
92481555	Flash light kit	100
92481829	Front weights Kg. 120 (Cannot be fitted on machines with front lift)	940
Front weights can be mounted on both sides of the engine		
92481930	Front bumper (Cannot be fitted on machines with front lift)	730
92480923	Weights for wheels 18" - 20" Kg. 50 each (pair)	680

Tractors VEGA

TRACTORS VEGA L80 and K105 SDT TIER 3B

STANDARD MACHINE

• OS-FRAME

- Synchronized gearbox: 32 speeds (16 FWD and 16 REV) with synchronized reverser
- Independent 2-speed rear PTO 540/540E r.p.m., with electro-hydraulically controlled wet multi-disc clutch and PTO synchronized with forward movement
- Flywheel with long-travel torsional damper
- Oil-immersed multi-disc transmission clutch, electronic hydraulic control, and **PRO-ACT System**
- 4-wheel drive: front wheels electro-hydraulic disengagement
- Differential locks: simultaneous front and rear or rear only with electro-hydraulic control
- Oil-immersed multi-disc brakes with hydrostatic control
- Independent oil-immersed, multi-disc parking brake
- Driving position with platform suspended on silent-block device
- Operator's position with suspended brakes/clutch pedals fitted on control column
- Tilting steering wheel with adjustable height
- Double-circuit hydraulic system with separate pumps and heat exchanger
K105: lift and control valves **27,7 l/min** - hydroguide and controls **33,1 l/min**
L80 : lift and control valves **29,5 l/min** - hydroguide and controls **33,5 l/min**
- Rear hydraulic lift by rams with ordinary hitches cat. 1 and 2 - Lifting capacity 2700 kg
- **Control valves: 2 double acting control valves without lockable delivery position** (1 or 2 double acting hydraulic control valves with lockable position can be required)
- Protection for engine oil pan
- Front and rear towing hooks
- 12V electric system with safety switch, lighting system, stop/direction indicators and rear working light
- Flash light setup
- Digital instrument panel with multi-function colour display and hour counter, battery and consumption level, **Diesel Particulate Filter level (K105)**, simultaneous reading of motor revolutions, forward and PTO speed. Warning lights and sound signal.
- Adjustable seat with spring suspension and safety belts
- Integrated cyclone prefilter with high-performance air filter and front air intake
- Folding roll-bar, EC approved
- Wheels 260/70-16 * 300/70-20 adjustable rim
- EC type approved to 40 km/h
- Complying with regulation 167/2013 EU (Mother Regulation)



VEGA L80 SDT STEERING WHEELS

• Power steering with dual rams acting on front wheelsi
4-CYLINDER ENGINE TURBO INTERCOOLER KOHLER KDI 2504 TCR
Direct injection - with counter-rotating balancing weights
55,4 KW / 75,3 HP WATER COOLING

Euro

TA9AZ110

52.740

VEGA L80 SDT DUALSTEER

•4-cylinder hydrostatic double steering acting on front wheels and articulated joint
4-CYLINDER ENGINE TURBO INTERCOOLER KOHLER KDI 2504 TCR
Direct injection - with counter-rotating balancing weights
55,4 KW / 75,3 HP WATER COOLING

Euro

TB0AZ110

54.590

VEGA K105 SDT STEERING WHEELS

• Power steering with dual rams acting on front wheelsi
4-CYLINDER ENGINE TURBO KUBOTA V3800 CR-T-E4B
Direct injection - with counter-rotating balancing weights
72,1 KW / 98 HP WATER COOLING

Euro

T0ZBE110

56.960

VEGA K105 SDT DUALSTEER

•4-cylinder hydrostatic double steering acting on front wheels and articulated joint
4-CYLINDER ENGINE TURBO KUBOTA V3800 CR-T-E4B
Direct injection - with counter-rotating balancing weights
72,1 KW / 98 HP WATER COOLING

Euro

TA0BE110

58.820

Price surcharge for non-standard wheels		Euro
*****	Wheels 260/70-16 * 340/65-20 adjustable rim	310
*****	Wheels 280/70-18 * 360/70-20 adjustable rim	620
*****	Wheels 280/70-18 * 320/70-24 adjustable rim	830
*****	Wheels 320/65-18 * 380/70-20 adjustable rim	730
*****	Wheels 340/65-18 * 420/65-24 adjustable rim	3.010

Control valves for lift by rams (in addition to the standard ones)		
92481944	1 single acting and 1 double acting control valve without lockable position (Max 2 double acting control valves with lockable position can be fitted, including the standard one)	780
92481945	1 double acting control valve without lockable position and 1 double acting control valve with float (A double acting control valve with lockable position cannot be required)	780

Control valves for lift with position and draft control (in addition to the standard ones)		
92481946	1 single acting and 1 double acting control valve without lockable position (Max 2 double acting control valves with lockable position can be fitted, including the standard one)	780
92481947	1 double acting control valve without lockable position and 1 double acting control valve with float (A double acting control valve with lockable position cannot be required)	780

AIRTECH Compact Cabin

***** Cabin with integrated monocoque body fitted on silent block.

Cat. 4 pressurization system and homologation (active carbon filter 92481948 required)

Rear glass can be opened, with rear "window" for passage of pipes. Glass doors with central plastic profile
Lower glass closing for better visibility of the ground from the front of the cabin. Ventilation and heating system. Air conditioning system with recycling device and ventilation nozzles integrated in the front of the cabin to get the best air conditioning and visibility also in the rear of the tractor. Car-type instrument panel and air takes. Dust filters. Front windscreen wiper and washer. Adjustable rear working lights. Flashing light. Fabric cover seat instead of standard one.

(BRAKE-OFF system compulsory)
(Cannot be used with Grammer seat)

11.240

92481948	Active carbon filter needed for cabin pressurization (pair)	700
-----------------	---	------------

Price surcharge for non-standard accessories

*****	Third point with quick couplings cat. 1 and 2 - Arms without adjustable length	320
*****	Third point with quick couplings, L-shaped, cat. 1 and 2 - Arms with adjustable length and hooks with adjustable width	680
*****	Automatic independent BRAKE-OFF parking brake (Required with cabin)	600
*****	Towing hook EC	230
*****	Towing hook EC with Slider frame	520
*****	Towing hook CUNA with Slider frame	520
*****	Cast-iron rim flanges kg. 140 (pair) for rear wheels 24"	770
*****	Electro-hydraulic reverser EasyDrive® , instead of the standard mechanical one, with lever control on the left of the steering wheel (Grammer pneumatic seat compulsory for tractors without cabin)	3.640

*****	Electronic joystick including 1 single acting control valve with adjustable flow and free return, 3 double acting control valves on the tractor rear side (replacing the standard ones), oversized pump 49 lt/min instead of the standard one. Joystick potentiometer. (The joystick cannot be used with the hydraulic lift with position/draft control) (Only with cabin)	5.620
*****	Oversized pump (replacing the standard one) to lift and control valves 48,8 lt/min (K105) - 51 lt/min (L80)	160
*****	Hydraulic lift strut and tie system	480
*****	Grammer pneumatic seat with safety belts (Cannot be used with cabin) (Compulsory for tractors without cabin and with reverser)	520
*****	Kab Seating (cannot be used with cabin and electro-hydraulic reverser)	330
*****	Lift with position and draft control (Cannot be used with the joystick) (Two double acting control valves without lockable position are provided - lockable position not possible)	780
*****	"Special Edition" black & white colour	1.140

Accessories

*****	Front lift with front protection and 2 double acting control valves with free return (1 additional single acting and 1 additional double acting control valve needed, except when using the joystick) (Cannot be used with front weights and bumper)	3.070
92481930	Front bumper (Cannot be fitted on machines with front lift and front plate for implements connection)	730
92481555	Flash light kit (for tractors without cabin)	100
92481971	Front plate for implements connection (Cannot be used with front bumper and lift)	210
92481829	Front weights Kg. 120 (Cannot be fitted on machines with front lift)	940

Front weights can be mounted on both sides of the engine

92480923	Weights for front wheels 18" - 20" Kg. 50 each (pair)	680
----------	---	-----

TRACTORS VEGA L80 and K105 AR REVERSIBLE TIER 3B

STANDARD MACHINE

- With central articulation and **OS-FRAME**
- Synchronized gearbox: 32 speeds (16 FWD and 16 REV) with synchronized reverser
- Independent 2-speed rear PTO 540/540E r.p.m., with electro-hydraulically controlled wet multi-disc clutch and PTO synchronized with forward movement
- Flywheel with long-travel torsional damper
- Wet multi-disc transmission clutch, electronic hydraulic control and **PRO-ACT System**
- 4-wheel drive: front wheels electro-hydraulic disengagement
- Differential locks: simultaneous front and rear or rear only with electro-hydraulic control
- Oil-immersed multi-disc brakes with hydrostatic control
- Automatic independent **BRAKE-OFF** parking brake
- Driving position with platform suspended on silent-block device
- Reversible operator's position with rotating platform and suspended brakes/clutch pedals fitted on rotating control column
- Power steering with dual-rams acting on central articulated joint
- Tilting steering wheel with adjustable height
- Double-circuit hydraulic system with separate pumps and heat exchanger
K105: lift and control valves **27,7 l/min** - hydroguide and controls **33,1 l/min**
L80 : lift and control valves **29,5 l/min** - hydroguide and controls **33,5 l/min**
- Rear hydraulic lift by rams with ordinary hitches cat. 1 and 2 - Lifting capacity 2300 kg.
- **Control valves: 2 double acting control valves without lockable delivery position, with oil recovery** (1 or 2 double acting hydraulic control valves with lockable position can be required)
- Protection for engine oil pan
- Front and rear towing hooks
- 12V electric system with safety switch, lighting system, stop/direction indicators and rear working light
- Flash light setup
- Digital instrument panel with multi-function colour display and hour counter, battery and consumption level, **Diesel Particulate Filter level (K105)**, simultaneous reading of motor revolutions, forward and PTO speed. Warning lights and sound signal.
- Adjustable seat with spring suspension, special lifting system and safety belts
- Integrated cyclone prefilter with high-performance air filter and front air intake
- Folding roll-bar, EC approved
- Wheels 250/80-18 adjustable rim
- EC type approved to 40 km/h
- Compliant with regulation 167/2013 EU (Mother Regulation)

VEGA L80 AR

4-CYLINDER ENGINE TURBO INTERCOOLER KOHLER KDI 2504 TCR

Direct injection - with counter-rotating balancing weights

55,4 KW / 75,3 HP WATER COOLING

Euro

TA6AZ150

51.500

VEGA K105 AR

4-CYLINDER ENGINE TURBO KUBOTA V3800 CR-T-E4B

Direct injection - with counter-rotating balancing weights

72,1 KW / 98 HP WATER COOLING

Euro

T0VBE150

55.730

Price surcharge for non-standard wheels

Euro

*****	Wheels 280/70-18 adjustable rim	370
*****	Wheels 320/65-18 adjustable rim	680
*****	Wheels 9.50-20 (250/85-20) adjustable rim	370
*****	Wheels 300/70-20 adjustable rim	890
*****	Wheels 320/70-20 adjustable rim (cannot be used with cabin)	1.040
*****	Wheels 340/65-20 adjustable rim	1.300
*****	Wheels Terra-Tyre 31x15.50-15 XTC fixed rim	580
*****	Wheels Terra-Tyre 31x15.50-15 STG fixed rim	580
*****	Wheels 33x12.50-15 T413 fixed rim	2.340

Control valves for lift by rams (in addition to the standard ones)

92481949	1 single acting control valve, 1 a doppio effetto without lockable position (Max 2 double acting control valves with lockable position can be fitted, including the standard one)	990
92481950	1 double acting control valve without lockable position and 1 double acting control valve with float (Max 2 double acting control valves with lockable position can be fitted, including the standard one)	990

Control valves for lift with position and draft control (in addition to the standard ones)

92481951	1 single acting and 1 double acting control valve without lockable position (Max 2 double acting control valves with lockable position can be fitted, including the standard one)	990
92481952	1 double acting control valve without lockable position and 1 double acting control valve with float (Max 2 double acting control valves with lockable position can be fitted, including the standard one)	990

Cabins

*****	<p>Comfort cabin, fully approved for safety and noise, with monocoque body fitted on silent-block device. Front and rear glasses can be opened - rear window for passage of pipes. Glass doors with central plastic profile. Lower glass closures for optimum visibility of the ground from the front of the cabin. Ventilation and heating system with easily accesible dust filter, removable and replaceable without tools. Front and rear windscreen wiper and washer. Fixed front working lights, moveable rear working lights. Rear view mirrors. Flashing light. Car radio slot. Porthole on rear side of sun roof. Air conditioning with evaporator on rear side of sun roof. Fabric covered seat instead of standard one</p>	9.160
*****	<p>Comfort cabin CONICAL VERSION</p> <p>(Cabins cannot be fitted on 320/70-20)</p>	9.680

92481548	Active carbon filter for cabin	150
92481766	Active carbon filter for CONICAL cabin	110

Price surcharge for non-standard attachments

*****	Third point with quick couplings, L-shaped, cat. 1 and 2 - Arms with adjustable length and hooks with adjustable width	730
*****	Towing hook EC	230
*****	Towing hook EC with Slider frame	520
*****	Towing hook CUNA with Slider frame	520
*****	Electro-hydraulic reverser EasyDrive® , instead of the standard mechanical one, with lever control on the left of the steering wheel (Grammer pneumatic seat compulsory) (Cannot be used with Kab Seating)	3.640
*****	Electronic joystick including 1 single acting control valve with adjustable flow and free return, 5 double acting control valves (replacing the standard ones) and oversized pump 49 lt/min instead of the standard one. Joystick potentiometer. (The joystick cannot be used with the hydraulic lift with position/draft control and the Kab Seating)	5.720
*****	Oversized pump (replacing the standard one) to lift and control valves: 48,8 lt/min (K105) - 51 lt/min (L80)	160
*****	Hydraulic lift strut and tie system	480
*****	Kab Seating (Cannot be used with the joystick)(Cannot be used with the reverser)	330
*****	Grammer pneumatic seat with safety belts (Compulsory with reverser)	520
*****	Lift with position and draft control (Cannot be used with the joystick) (Two double acting control valves without lockable position are provided) (1 or 2 double acting hydraulic control valves with lockable position can be required - max 2 besides the standard ones)	700
*****	"Special Edition" black & white colour	1.140

Accessories

*****	Front lift with front protection and 2 double acting control valves with free return (1 additional single acting and 1 additional double acting control valve needed, except when using the joystick) (Cannot be used with front weights and bumper)	3.070
92481555	Flash light kit (for tractors without cabin)	100
92481930	Front bumper (Cannot be fitted on machines with front lift)	730
92481829	Front weights Kg.120 (Cannot be fitted on machines with front lift)	940
Front weights can be mounted on both sides of the engine		
92480923	Weights for wheels 18" - 20" Kg. 50 each (pair)	680

TRACTORS VEGA L80 and K105 RS REVERSIBLE TIER 3B

STANDARD MACHINE

- Rigid, front steering wheels and **OS-FRAME**
- Synchronized gearbox: 32 speeds (16 FWD and 16 REV) with synchronized reverser
- Independent 2-speed rear PTO 540/540E r.p.m., with electro-hydraulically controlled wet multi-disc clutch and PTO synchronized with forward movement
- Flywheel with long-travel torsional damper
- Oil-immersed multi-disc transmission clutch, electronic hydraulic control and **PRO-ACT System**
- 4-wheel drive: front wheels electro-hydraulic disengagement
- Differential locks: simultaneous front and rear or rear only with electro-hydraulic control
- Oil-immersed multi-disc brakes with hydrostatic control
- Automatic independent **BRAKE-OFF** parking brake
- Driving position with platform suspended on silent-block device
- Reversible operator's position with rotating platform and suspended brakes/clutch pedals fitted on rotating control column
- Power steering with dual-rams acting on front wheels
- Tilting steering wheel with adjustable height
- Double-circuit hydraulic system with separate pumps and heat exchanger
K105: lift and control valves **27,7 l/min** - hydroguide and controls **33,1 l/min**
L80 : lift and control valves **29,5 l/min** - hydroguide and controls **33,5 l/min**
- Rear hydraulic lift by rams with ordinary hitches cat. 1 and 2 - Lifting capacity 2300 kg
- **Control valves: 2 double acting control valves without lockable delivery position** (1 or 2 double acting hydraulic control valves with lockable position can be required)
- Protection for engine oil pan
- Front and rear towing hooks
- 12V electric system with safety switch, lighting system, stop/direction indicators and rear working light
- Flash light setup
- Digital instrument panel with multi-function colour display and hour counter, battery and consumption level, **Diesel Particulate Filter level (K105)**, simultaneous reading of motor revolutions, forward and PTO speed. Warning lights and sound signal.
- Adjustable seat with spring suspension, special lifting system and safety belts
- Integrated cyclone prefilter with high-performance air filter and front air intake
- Folding roll-bar, EC approved
- Wheels 280/70-18 adjustable rim
- EC type approved to 40 km/h
- Complying with regulation 167/2013 EU (Mother Regulation)



VEGA L80 RS

4-CYLINDER ENGINE TURBO INTERCOOLER KOHLER KDI 2504 TCR Euro
 Direct injection - with counter-rotating balancing weights
 55,4 KW / 75,3 HP WATER COOLING

TA7AZ15A **52.230**

VEGA K105 RS

4-CYLINDER ENGINE TURBO KUBOTA V3800 CR-T-E4B Euro
 Direct injection - with counter-rotating balancing weights
 72,1 KW / 98 HP WATER COOLING

T0WBE15A **56.450**

Price surcharge for non-standard wheels Euro

*****	Wheels 9.50-20 (250/85-20) adjustable rim	no price surcharge
*****	Wheels 320/65-18 adjustable rim	310
*****	Wheels 340/65-18 adjustable rim	2.080
*****	Wheels 300/70-20 adjustable rim	520
*****	Wheels 320/70-20 adjustable rim	670
*****	Wheels 340/65-20 adjustable rim	930
*****	Wheels 31x15.50-15 XTC fixed rim	210
*****	Wheels 31x15.50-15 STG fixed rim	210
*****	Wheels 13.6-16 Garden fixed rim	1.970

Control valves for lift by rams (in addition to the standard ones)

92481953	1 single acting control valve, 1 a doppio effetto without lockable position (Max 2 double acting control valves with lockable position can be fitted, including the standard one)	890
92481954	1 double acting control valve without lockable position and 1 double acting control valve with float (Max 2 double acting control valves with lockable position can be fitted, including the standard one)	890

Control valves for lift with position and draft control (in addition to the standard ones)

92481955	1 single acting and 1 double acting control valve without lockable position (Max 2 double acting control valves with lockable position can be fitted, including the standard one)	890
92481956	1 double acting control valve without lockable position and 1 double acting control valve with float (Max 2 double acting control valves with lockable position can be fitted, including the standard one)	890

Cabins

*****	Comfort cabin, fully approved for safety and noise, with monocoque body fitted on silent-block device. Front and rear glasses can be opened - rear window for passage of pipes. Glass doors with central plastic profile. Lower glass closures for optimum visibility of the ground from the front of the cabin. Ventilation and heating system with easily accesible dust filter, removable and replaceable without tools. Front and rear windscreen wiper and washer. Fixed front working lights, moveable rear working lights. Rear view mirrors. Flashing light. Car radio slot. Porthole on rear side of sun roof. Air conditioning with evaporator on rear side of sun roof. Fabric covered seat instead of standard one	9.160
*****	Comfort cabin CONICAL VERSION	9.680
92481548	Active carbon filter for cabin	150
92481766	Active carbon filter for CONICAL cabin	110

Price surcharge for non-standard accessories

*****	Third point with quick couplings cat. 1 and 2 - Arms with adjustable length	390
*****	Third point with quick couplings, L-shaped, cat. 1 and 2 - Arms with adjustable length and hooks with adjustable width	730
*****	Towing hook EC	230
*****	Towing hook EC with Slider frame	520
*****	Towing hook CUNA with Slider frame	520
*****	Electro-hydraulic reverser EasyDrive® , instead of the standard mechanical one, with lever control on the left of the steering wheel (Grammer pneumatic seat compulsory) (Cannot be used with Kab Seating)	3.640
*****	Electronic joystick including 1 single acting control valve with adjustable flow and free return, 5 double acting control valves (replacing the standard ones) and oversized pump 49 lt/min instead of the standard one. Joystick potentiometer. (The joystick cannot be used with the hydraulic lift with position/draft control and the Kab Seating)	5.200
*****	Oversized pump (replacing the standard one) to lift and control valves: 48,8 lt/mnin (K105) - 51 lt/min (L80)	160
*****	Hydraulic lift strut and tie system	480
*****	Kab Seating (Cannot be used with the joystick)(Cannot be used with reverser)	330
*****	Grammer pneumatic seat with safety belts (Compulsory with reverser)	520
*****	Lift with position and draft control (Cannot be used with the joystick) (Two double acting control valves without lockable position are provided) (1 or 2 double acting hydraulic control valves with lockable position can be required - max 2 besides the standard ones)	700
*****	"Special Edition" black & white colour	1.140

Accessories

*****	Front lift with front protection and 2 double acting control valves with free return (1 additional single acting and 1 additional double acting control valve needed, except when using the joystick) (Cannot be used with front weights and bumper)	3.070
92481555	Flash light kit (for tractors without cabin)	100
92481930	Front bumper (Cannot be fitted on machines with front lift)	730
92481829	Front weights Kg.120 (Cannot be fitted on machines with front lift)	940
Front weights can be mounted on both sides of the engine		
92480923	Weights for wheels 18" - 20" Kg. 50 each (pair)	680

TRACTORS VEGA L80 and K105 DUALSTEER REVERSIBLE TIER 3B

STANDARD MACHINE

- **4-cylinder DUALSTEER** system, with **OS-FRAME**
- Synchronized gearbox: 32 speeds (16 FWD and 16 REV) with synchronized reverser
- Independent 2-speed rear PTO 540/540E r.p.m., with electro-hydraulically controlled wet multi-disc clutch and PTO synchronized with forward movement
- Flywheel with long-travel torsional damper
- Oil-immersed multi-disc transmission clutch, electronic hydraulic control and **PRO-ACT System**
- 4-wheel drive: front wheels electro-hydraulic disengagement
- Differential locks: simultaneous front and rear or rear only with electro-hydraulic control
- Oil-immersed multi-disc brakes with hydrostatic control
- Automatic independent **BRAKE-OFF** parking brake
- Driving position with platform suspended on silent-block device
- Reversible operator's position with rotating platform and suspended brakes/clutch pedals fitted on rotating control column
- Hydrostatic double steering acting on front wheels and central articulated joint
- Steering wheel with adjustable height
- Double-circuit hydraulic system with separate pumps and heat exchanger
K105: lift and control valves **27,7 l/min** - hydroguide and controls **33,1 l/min**
L80 : lift and control valves **29,5 l/min** - hydroguide and controls **33,5 l/min**
- Rear hydraulic lift by rams with ordinary hitches cat. 1 and 2 -Lifting capacity 2300 kg.
- **Control valves: 2 double acting control valves without lockable delivery position**
(1 or 2 double acting hydraulic control valves with lockable position can be required)
- Protection for engine oil pan
- Front and rear towing hooks
- 12V electric system with safety switch, lighting system, stop/direction indicators and rear working light
- Flash light setup
- Digital instrument panel with multi-function colour display and hour counter, battery and consumption level, **Diesel Particulate Filter level (K105)**, simultaneous reading of motor revolutions, forward and PTO speed. Warning lights and sound signal.
- Adjustable seat with spring suspension, special lifting system and safety belts
- Integrated cyclone prefilter with high-performance air filter and front air intake
- Folding roll-bar, EC approved
- Wheels 280/70-18 adjustable rim
- EC type approved to 40 km/h
- Complying with regulation 167/2013 EU (Mother Regulation)

VEGA L80 DUALSTEER

4-CYLINDER ENGINE TURBO INTERCOOLER KOHLER KDI 2504 TCR Euro
 Direct injection - with counter-rotating balancing weights
 55,4 KW / 75,3 HP WATER COOLING

TA8AZ15A **54.180**

VEGA K105 DUALSTEER

4-CYLINDER ENGINE TURBO KUBOTA V3800 CR-T-E4B Euro
 Direct injection - with counter-rotating balancing weights
 72,1 KW / 98 HP WATER COOLING

T0YBE15A **58.410**

Price surcharge for non-standard wheels	Euro
***** Wheels 9.50-20 (250/85-20) adjustable rim	no price surcharge
***** Wheels 320/65-18 adjustable rim	310
***** Wheels 340/65-18 adjustable rim	2.080
***** Wheels 300/70-20 adjustable rim	520
***** Wheels 320/70-20 adjustable rim	670
***** Wheels 340/65-20 adjustable rim	930
***** Wheels 31x15.50-15 XTC fixed rim	210
***** Wheels 31x15.50-15 STG fixed rim	210
***** Wheels 13.6-16 Garden fixed rim	1.970

Control valves for lift by rams (in addition to the standard ones)

92481953	1 single acting control valve, 1 a doppio effetto without lockable position (Max 2 double acting control valves with lockable position can be fitted, including the standard one)	890
92481954	1 double acting control valve without lockable position and 1 double acting control valve with float (Max 2 double acting control valves with lockable position can be fitted, including the standard one)	890

Control valves for lift with position and draft control (in addition to the standard ones)

92481955	1 single acting and 1 double acting control valve without lockable position (Max 2 double acting control valves with lockable position can be fitted, including the standard one)	890
92481956	1 double acting control valve without lockable position and 1 double acting control valve with float (Max 2 double acting control valves with lockable position can be fitted, including the standard one)	890

Cabins

*****	Comfort cabin, fully approved for safety and noise, with monocoque body fitted on silent-block device. Front and rear glasses can be opened - rear window for passage of pipes. Glass doors with central plastic profile. Lower glass closures for optimum visibility of the ground from the front of the cabin. Ventilation and heating system with easily accesible dust filter, removable and replaceable without tools. Front and rear windscreen wiper and washer. Fixed front working lights, moveable rear working lights. Rear view mirrors. Flashing light. Car radio slot. Porthole on rear side of sun roof. Air conditioning with evaporator on rear side of sun roof. Fabric covered seat instead of standard one	9.160
*****	Comfort cabin CONICAL VERSION	9.680
92481548	Active carbon filter for cabin	150
92481766	Active carbon filter for CONICAL cabin	110

Price surcharge for non-standard accessories

*****	Third point with quick couplings, L-shaped, cat. 1 and 2 - Arms with adjustable length	390
*****	Third point with quick couplings, L-shaped, cat. 1 and 2 - Arms with adjustable length and hooks with adjustable width	730
*****	Towing hook EC	230
*****	Towing hook EC with Slider frame	520
*****	Towing hook CUNA with Slider frame	520
*****	Electro-hydraulic reverser EasyDrive® , instead of the standard mechanical one, with lever control on the left of the steering wheel (Grammer pneumatic seat compulsory) (Cannot be used with Kab Seating)	3.640
*****	Electronic joystick including 1 single acting control valve with adjustable flow and free return, 5 double acting control valves (replacing the standard ones) and oversized pump 49 lt/min instead of the standard one. Joystick potentiometer. (The joystick cannot be used with the hydraulic lift with position/draft control and the Kab Seating)	5.200
*****	Oversized pump (replacing the standard one) to lift and control valves: 48,8 lt/min (K105) - 51 lt/min (L80)	160
*****	Hydraulic lift strut and tie system	480
*****	Kab Seating (Cannot be used with the joystick)(Cannot be used with reverser)	330
*****	Grammer pneumatic seat with safety belts (Compulsory with reverser)	520
*****	Lift with position and draft control (Cannot be used with the joystick) (Two double acting control valves without lockable position are provided) (1 or 2 double acting hydraulic control valves with lockable position can be required - max 2 besides the standard ones)	700
*****	"Special Edition" black & white colour	1.140

Accessories

*****	Front lift with front protection and 2 double acting control valves with free return (1 additional single acting and 1 additional double acting control valve needed, except when using the joystick) (Cannot be used with front weights and bumper)	3.070
92481555	Flash light kit (for tractors without cabin)	100
92481930	Front bumper (Cannot be fitted on machines with front lift)	730
92481829	Front weights Kg.120 (Cannot be fitted on machines with front lift)	940
Front weights can be mounted on both sides of the engine		
92480923	Weights for wheels 18" - 20" Kg. 50 each (pair)	680

TRACTORS VEGA L80 (NEW) AND K105 MT

STANDARD MACHINE

REVERSIBLE TIER 3B

• **OS-FRAME – Haymaking version**

- Front steering wheels, with OS-FRAME
- Synchronized gearbox: 32 speeds (16 FWD and 16 REV) with synchronized reverser
- Independent 2-speed rear PTO 540/1000 r.p.m., with electro-hydraulically controlled wet multi-disc clutch and PTO synchronized with forward movement
- Flywheel with long-travel torsional damper
- Oil-immersed multi-disc transmission clutch, electronic hydraulic control and **PRO-ACT System**
- 4-wheel drive: front wheels electro-hydraulic disengagement
- Differential locks: simultaneous front and rear or rear only with electro-hydraulic control
- Oil-immersed multi-disc brakes with hydrostatic control
- Automatic independent **BRAKE-OFF** parking brake
- Driving position in wider version with suspended platform on silent-block
- Reversible operator's position with rotating platform and suspended brakes/clutch pedals fitted on rotating control column
- Power steering with dual-rams acting on front wheels
- Tilting steering wheel with adjustable height
- Double-circuit hydraulic system with separate pumps and heat exchanger
K105: lift and control valves **27,7 l/min** - hydroguide and controls **33,1 l/min**
L80 : lift and control valves **29,5 l/min** - hydroguide and controls **33,5 l/min**
- Rear hydraulic lift by rams with quick couplers, arms with adjustable length cat. 1 and 2 and hooks with adjustable width - Lifting capacity 2300 kg
- **Control valves: 1 single acting and 2 double acting control valves without lockable delivery position** (1 or 2 double acting hydraulic control valves with lockable position can be required)
- **Dual Floating System**
- **Hydraulic suspension HDR**
- Protection for engine oil pan
- Front and rear towing hooks
- 12V electric system with safety switch, lighting system, stop and direction indicators

- Digital instrument panel with multi-function colour display and hour counter, battery and consumption level, Diesel Particulate Filter level, simultaneous reading of motor revolutions, forward and PTO speed. Warning lights and sound signal.
- Adjustable seat with spring suspension, specila lifting system and safety belts
- Integrated cyclone prefilter with high-performance air filter and front air intake
- Semi-cabin with roll over protection and headlights, rear view mirrors, flash light and front/rear windscreen wiper and washer
- Wheels 31x15.50-15 XTC fixed rim
- EC type approved to 40 km/h
- Complying with regulation 167/2013 EU (Mother Regulation)

VEGA L80 MT

4-CYLINDER ENGINE TURBO INTERCOOLER KOHLER KDI 2504 TCR
Direct injection - with counter-rotating balancing weights
55,4 KW / 75,3 HP WATER COOLING

Euro

TB1AZ110

57.790

VEGA K105 MT

4-CYLINDER ENGINE TURBO KUBOTA V3800 CR-T-E4B
Direct injection - with counter-rotating balancing weights
72,1 KW / 98 HP WATER COOLING

Euro

TOXB110

62.010

Price surcharge for non-standard wheels

Euro

*****	Wheels 31x15.50-15 STG fixed rim	no price surcharge
*****	Wheels 440/50-17 All-Ground fixed rim	1.760
*****	Wheels 425/55-17 AC70G fixed rim	1.970
*****	Wheels 340/65-20 adjustable rim	720

Control valves (in addition to the standard ones (one valve max.))

92481957	1 single acting control valve	330
92481958	Double acting control valve without lockable position (Max 2 double acting control valves with lockable position can be fitted, including the standard one)	330
92481959	Double acting control valve with float	330

Cabins

Comfort cabin, fully approved for safety and noise, with monocoque body fitted on silent-block device. Front and rear glasses can be opened - rear window for passage of pipes. Glass doors with central plastic profile. Lower glass closures for optimum visibility of the ground from the front of the cabin. Ventilation and heating system with easily accessible dust filter, removable and replaceable without tools. Front and rear windscreen wiper and washer. Fixed front working lights, moveable rear working lights. Rear view mirrors. Flashing light. Car radio slot. Porthole on rear side of sun roof. Air conditioning with evaporator on rear side of sun roof. Fabric covered seat with armrest instead of standard one.

5.620

924.81548 Active carbon filter for cabin
150

Price surcharge for non-standard accessories

*****	Towing hook EC	230
*****	Towing hook EC with Slider frame	520
*****	Towing hook CUNA with Slider frame	520
*****	Electro-hydraulic reverser EasyDrive® , instead of the standard mechanical one, with lever control on the left of the steering wheel (Grammer pneumatic seat compulsory)	3.640
*****	Electronic joystick including 1 single acting control valve without free return and 3 double acting control valves (replacing the standard ones). Joystick potentiometer.	5.200
*****	Hydraulic lift strut and tie system	480
*****	Grammer pneumatic seat with safety belts (Compulsory with reverser)	520
*****	"Special Edition" black & white colour	1.140

Accessories

*****	Front lift with front protection and 2 double acting control valves with free return (1 additional single acting and 1 additional double acting control valve needed, except when using the joystick) (Cannot be used with front weights and bumper)	3.070
92481930	Front bumper (Cannot be fitted on machines with front lift)	730
92481829	Front weights Kg. 120 (Cannot be fitted on machines with front lift)	940
Front weights can be mounted on both sides of the engine		
92480923	Weights for wheels 20" Kg. 50 each (pair)	680

TRACTORS VEGA SKY JUMP K105 DUALSTEER TIER 3B

STANDARD MACHINE

- 4-cylinder Dualsteer system and **OS-FRAME**
- Synchronized gearbox: 32 speeds (16 FWD and 16 REV) with synchronized reverser
- Independent 2-speed rear PTO 540/750 r.p.m., with electro-hydraulically controlled wet multi-disc clutch and PTO synchronized with forward movement
- Flywheel with long-travel torsional damper
- Oil-immersed multi-disc transmission clutch, electronic hydraulic control and **PRO-ACT System**
- 4-wheel drive: front wheels electro-hydraulic disengagement
- Differential locks: simultaneous front and rear or rear only with electro-hydraulic control
- Oil-immersed multi-disc brakes with hydrostatic control
- Automatic independent **BRAKE-OFF** parking brake
- Driving position with suspended platform on silent-block
- Operator's position with suspended brakes/clutch pedals fitted on control column
- Double steering with hydrostatic drive acting on front wheels and central articulation
- Double-circuit hydraulic system with independent pumps and heat exchanger
 - Rear hydraulic lift by rams with ordinary couplers cat. 1 and 2
- Lifting capacity 2700 kg
- **Control valves: 2 double acting control valves without lockable delivery position**
- Front and rear towing hooks
- 12V electric system with safety switch, lighting system, stop and direction indicators
- Safety devices complying with regulations
- Instrument panel with multi-functional, colour display and digital instrument with hour counter, battery and consumption level, Diesel Particulate Filter level, simultaneous reading of motor revolutions, forward and PTO speed. Warning lights and sound signal.
- Integrated cyclone prefilter with high-performance air filter and front air intake
- Adjustable seat with spring suspension and safety belts
- Compact cabin AIRTECH version with **pressurization system and homologation Cat. 4 (active carbon filter 92481948 required)**
- Front wheels 280/70-20 fixed rim - Rear rubber crawlers
Length mm. 1223; width mm. 305; external unit width mm. 1350
- EC type approved to 40 km/h
- Complying with regulation 167/2013 EU (Mother Regulation)

VEGA SKY JUMP K105 DUALSTEER

4-CYLINDER ENGINE TURBO KUBOTA V3800 CR-T-E4B
Direct injection - with counter-rotating balancing weights
72,1 KW / 98 HP WATER COOLING

Euro

TA1BE110K

86.520

Control valves for lift by rams (in addition to the standard ones)

92481944	1 single acting and 1 double acting control valves without lockable position (Max 2 double acting control valves with lockable position can be fitted, including the standard one)	780
-----------------	--	------------

92481945	1 double acting control valve without lockable position and 1 double acting control valve with float (Max 2 double acting control valves with lockable position can be fitted, including the standard one)	780
-----------------	--	------------

Control valves for lift with position and draft control (in addition to the standard ones)

92481946	1 single acting and 1 double acting control valve without lockable position (Max 2 double acting control valves with lockable position can be fitted, including the standard one)	780
-----------------	---	------------

92481947	1 double acting control valve without lockable position and 1 double acting control valve with float (Max 2 double acting control valves with lockable position can be fitted, including the standard one)	780
-----------------	--	------------

Price surcharge for non-standard accessories

*****	Third point with quick couplings cat. 1 and 2 - Arms without adjustable length	320
-------	--	------------

*****	Third point with quick couplings, L-shaped, cat. 1 and 2 - Arms with adjustable length and hooks with adjustable width	680
-------	--	------------

*****	Towing hook EC	230
-------	-----------------------	------------

*****	Towing hook EC with Slider frame	520
-------	---	------------

*****	Towing hook CUNA with Slider frame	520
-------	---	------------

*****	Electro-hydraulic reverser EasyDrive® , instead of the standard mechanical one, with lever control on the left of the steering wheel (Grammer pneumatic seat standard)	3.640
*****	Electronic joystick including 1 single acting control valve with free return and 3 double acting control valves in the rear side of the tractor (replacing the standard ones), oversize pump 49 lt/min (replacing the standard one) , Joystick potentiometer. (Cannot be fitted on the machine with position and draft control) (Can be used with cabin only)	5.620
*****	Oversize pump 49 lt/min. replacing the serial one (standard with joystick)	160
*****	Hydraulic lift strut and tie system	480
*****	Hydraulic lift with position and draft control (Cannot be fitted with joystick) (2 double acting control valves WITHOUT lockable position are supplied as standard. It is not possible to require them with lockable position)	780
*****	"Special Edition" black & white colour	1.140

Accessories

*****	Front lift with front protection and 2 double acting control valves with free return (1 additional single acting and 1 additional double acting control valve needed, except when using the joystick) (Cannot be used with front weights and bumper)	3.070
92481948	Active carbon filter for pressurized cabin	700
92481930	Front bumper (Cannot be fitted on machines with front lift and kit front plate to fit accessories)	730
92481971	Kit front plate to fit accessories (Cannot be fitted on machines with front bumper and front lift)	210
92481829	Front weights Kg. 120 (Cannot be fitted on machines with front lift)	940
Front weights can be mounted on both sides of the engine		
92480923	Weights for wheels 20" Kg. 50 each (pair)	680

ENGINE SPECIFICATIONS

ENGINE	MODEL	CAPACITY CM ³	CYLINDER	HP / KW		COOLING	FUEL
LOMBARDINI	LDW 1404	1372	4	35	25,5	WATER	DIESEL
KUBOTA	D 1105	1123	3	25,2	18,6	WATER	DIESEL
	V 1505	1498	4	35,6	26,2		
	V 2203	2197	4	48	35,2		
	V 3800	3769	4	98	72,1		
KOHLER	KDI 2504M	2504	4	49	36	WATER	DIESEL
	KDI 2504TCR			75,3	55,4		

NOTES



BCS S.p.A.

Viale Mazzini, 161 - 20081 Abbiategrasso (Milano)

Tel. +39 02 94821 - Fax +39 02 94960800 - info@bcs-ferrari.it

www.ferrariagri.it